



工业电源

导轨型电源

经济型

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
CHROME II  <ul style="list-style-type: none"> 符合 DIN43880 安装要求 Class II, 双重绝缘 具备 IEC 60335 / IEC 61558 安规认证 符合 DOE Level VI 的二氧化碳排放要求 符合 NEC Class 2 / LPS 法规 	DRC-05V015W1RZ 新品	●	5 V	2.4 A	12 W	85-264 V _{AC}	87.5 × 18 × 55
	DRC-05V030W1RZ 新品			3.0 A	15 W		87.5 × 35 × 55
	DRC-12V015W1RZ 新品	●	12 V	1.25 A	15 W	85-264 V _{AC}	87.5 × 18 × 55
	DRC-12V030W1RZ			2.0 A	24 W		87.5 × 35 × 55
	DRC-12V060W1RZ			4.5 A	54 W		87.5 × 52.5 × 55
	DRC-12V100W1RZ			7.1 A	85.2 W		87.5 × 70 × 55
	DRC-24V015W1RZ 新品	●	24 V	0.63 A	15 W	85-264 V _{AC}	87.5 × 18 × 55
	DRC-24V030W1RZ			1.5 A	36 W		87.5 × 35 × 55
	DRC-24V060W1RZ			2.5 A	60 W		87.5 × 52.5 × 55
	DRC-24V100W1RZ			3.83 A	91.92 W		87.5 × 70 × 55
DRC-48V060W1RZ	●	48 V	1.25 A	60 W	85-264 V _{AC}	87.5 × 52.5 × 55	
DRC-48V100W1RZ			1.92 A	92.16 W		87.5 × 70 × 55	

经济型

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)	
			电压	电流	功率			
LYTE II / DIN Eco  <ul style="list-style-type: none"> LYTE II: 单相交流电输入 DIN Eco: 三相交流电输入 窄机身设计 内置恒流线路 50°C 满功率输出 低空载功耗 	DRL-12V75W1AZ□	●	12 V	6.25 A	75 W	85-264 V _{AC}	123.6 × 27 × 102	
	DRL-24V75W1AZ□		24 V	3.125 A	75 W	85-264 V _{AC}	123.6 × 27 × 102	
	DRL-48V75W1AZ□	●	12 V	48 V	1.57 A	75.36 W	85-264 V _{AC}	123.6 × 27 × 102
	DRL-12V120W1EN□			10.0 A	120 W	90-264 V _{AC}	123.6 × 30 × 116.8	
	DRL-12V240W1EN□			20.0 A	240 W		123.6 × 40 × 116.8	
	DRL-24V120W1EN□			5.0 A	120 W	123.6 × 30 × 116.8		
	DRL-24V240W1EN□	●	24 V	10.0 A	240 W	90-264 V _{AC}	123.6 × 40 × 116.8	
	DRL-24V480W1EN□			20.0 A	480 W		123.6 × 56 × 116.8	
	DRL-24V960W1EN□ 新品			40.0 A	960 W	85-277 V _{AC}	123.6 × 103.8 × 137	
	DRL-48V120W1EN□			2.5 A	120 W	123.6 × 30 × 116.8		
	DRL-48V240W1EN□	●	48 V	5.0 A	240 W	90-264 V _{AC}	123.6 × 40 × 116.8	
	DRL-48V480W1EN□			10.0 A	480 W		123.6 × 56 × 116.8	
	DRL-48V960W1EN□ 新品			20.0 A	960 W	85-277 V _{AC}	123.6 × 103.8 × 137	
	DRL-24V120W3EN 新品			5.0 A	120 W	3 × 340-575 V _{AC}	123.6 × 40 × 116.8	
	DRL-24V240W3EN 新品	10.0 A	240 W	123.6 × 56 × 116.8				
	DRL-24V480W3EN 新品	20.0 A	480 W	123.6 × 60 × 142.6				
	DRL-24V960W3EN 新品	40.0 A	960 W	123.6 × 110 × 142.6				
	DRL-48V120W3EN 新品	●	48 V	2.5 A	120 W	3 × 340-575 V _{AC}	123.6 × 40 × 116.8	
	DRL-48V240W3EN 新品			5.0 A	240 W		123.6 × 56 × 116.8	
	DRL-48V480W3EN 新品			10.0 A	480 W	123.6 × 60 × 142.6		
DRL-48V960W3EN 新品	20.0 A			960 W	123.6 × 110 × 142.6			

高性能

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
Force-GT  <ul style="list-style-type: none"> 窄机身设计, 效率高达 95% 内置恒流线路 三防胶涂布 60°C (单相) 和 55°C (三相) 满功率输出 	DRF-12V120W1G□A	●	12 V	10.0 A	120 W	90-264 V _{AC} (直流输入范围 127-375 V _{DC})	123.6 × 30 × 116.8
	DRF-12V240W1G□A			20.0 A	240 W		123.6 × 40 × 116.8
	DRF-24V120W1G□A	●	24 V	5.0 A	120 W	90-264 V _{AC} (直流输入范围 127-375 V _{DC})	123.6 × 30 × 116.8
	DRF-24V240W1G□A			10.0 A	240 W		123.6 × 40 × 116.8
	DRF-24V480W1G□A			20.0 A	480 W		123.6 × 56 × 116.8
	DRF-48V120W1G□A			2.5 A	120 W		123.6 × 30 × 116.8
	DRF-48V240W1G□A	●	48 V	5.0 A	240 W	90-264 V _{AC} (直流输入范围 127-375 V _{DC})	123.6 × 40 × 116.8
	DRF-48V480W1G□A			10.0 A	480 W		123.6 × 56 × 116.8
	DRF-24V120W3G□A			5.0 A	120 W	3 × 320-575 V _{AC} 或 2 × 340-575 V _{AC} (直流输入范围 450-800 V _{DC})	124 × 38 × 125.3
	DRF-24V240W3G□A			10.0 A	240 W		124 × 50 × 125.3
DRF-24V480W3G□A	20.0 A	480 W	124 × 65 × 127.3				
DRF-24V960W3G□A	40.0 A	960 W	124 × 110 × 128.7				
DRF-48V480W3G□A 新品	●	48 V	10.0 A	480 W	3 × 320-575 V _{AC} 或 2 × 340-575 V _{AC} (直流输入范围 450-800 V _{DC})	124 × 65 × 127.3	
DRF-48V960W3G□A 新品			20.0 A	960 W		124 × 110 × 128.7	
DIN Pro  <ul style="list-style-type: none"> 峰值功率达 150% / 5 秒 内建遥控开关 三防胶涂布 60°C 满功率输出 	DRF-12V120W1PBA 新品	●	12 V	10.0 A	120 W	85-277 V _{AC} (305 V _{AC} 60 秒) (直流输入范围 120-400 V _{DC})	124.2 × 30 × 117.1
	DRF-12V240W1PBA 新品			20.0 A	240 W		124.2 × 40 × 117.1
	DRF-24V120W1PBA 新品	●	24 V	5.0 A	120 W	85-277 V _{AC} (305 V _{AC} 60 秒) (直流输入范围 120-400 V _{DC})	124.2 × 30 × 117.1
	DRF-24V240W1PBA 新品			10.0 A	240 W		124.2 × 40 × 117.1
	DRF-24V480W1PBA 新品			20.0 A	480 W		124.2 × 56 × 117.1
	DRF-24V960W1PBA 新品			40.0 A	960 W		124.2 × 104.5 × 137.7
	DRF-48V120W1PBA 新品	●	48 V	2.5 A	120 W	85-277 V _{AC} (305 V _{AC} 60 秒) (直流输入范围 120-400 V _{DC})	124.2 × 30 × 117.1
	DRF-48V240W1PBA 新品			5.0 A	240 W		124.2 × 40 × 117.1
	DRF-48V480W1PBA 新品			10.0 A	480 W		124.2 × 56 × 117.1
	DRF-48V960W1PBA 新品			20.0 A	960 W		124.2 × 104.5 × 137.7

导轨型电源

特别设计

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (H × W × D)
			电压	电流	功率		
CliQ M  <ul style="list-style-type: none"> 通过海事认证 三防胶涂布 增强型峰值功率 (APB) 	DRM-24V80W1PN	●	24 V	3.4 A	81.6 W	85-276 V _{AC} (直流输入范围 88-375 V _{DC})	124 × 32 × 102
	DRM-24V120W1PN	●		5.0 A	120 W	85-264 V _{AC} (直流输入范围 88-375 V _{DC})	124 × 40 × 117
	DRM-24V240W1PN	●		10.0 A	240 W	85-276 V _{AC} (直流输入范围 88-375 V _{DC})	124 × 60 × 117
	DRM-24V480W1PN	●		20.0 A	480 W		124 × 82 × 127
	DRM-24V960W1PN	●		40.0 A	960 W	85-264 V _{AC} (直流输入范围 110-375 V _{DC})	124 × 125 × 133.6
	DRM-24V480W3PN	●		20.0 A	480 W	3 × 320-600 V _{AC} 或 2 × 380-600 V _{AC} (直流输入范围 450-800 V _{DC})	124 × 65 × 127.1
	DRM-24V960W3PN	●		40.0 A	960 W		124 × 110 × 128.6
CliQ VA  <ul style="list-style-type: none"> 智能监控输出电流/电压和寿命预期 三防胶涂布 增强型峰值功率 (APB) 	DRV-24V120W1PN	●	24 V	5.0 A	120 W	85-264 V _{AC} (直流输入范围 88-375 V _{DC})	124 × 60 × 139
	DRV-24V240W1PN	●		10.0 A	240 W	85-276 V _{AC} (直流输入范围 88-375 V _{DC})	124 × 60 × 139
	DRV-24V480W1PN	●		20.0 A	480 W		124 × 82 × 149

*对于可选项, 请参阅产品规格书