



工业电源

平板型电源


经济型

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)				
			电压	电流	功率						
PMT2 Eco  <ul style="list-style-type: none"> • 额定高压输入 200-240 V_{AC} • 符合 EMC Class A • CCC/CQC 和 BIS 认证 	PMT-24V50W2BNJ 新品		24 V	2.2 A	52.8 W	180-264 V _{AC}	99 × 82 × 29				
	PMT-24V75W2BNJ 新品			3.2 A	76.8 W		99 × 97 × 30				
	PMT-24V100W2BNJ 新品			4.5 A	108 W		129 × 97 × 30				
	PMT-24V150W2BNJ 新品			6.25 A	150 W		159 × 97 × 30				
	PMT-24V200W2BNJ 新品			8.8 A	211.2 W		159 × 97 × 30				
	PMT-24V350W2BNJ 新品			14.6 A	350.4 W		215 × 115 × 30				
		PMT-48V50W2BNJ 新品		48 V	1.1 A	52.8 W	180-264 V _{AC}	99 × 82 × 29			
		PMT-48V75W2BNJ 新品			1.6 A	76.8 W		99 × 97 × 30			
		PMT-48V100W2BNJ 新品			2.3 A	110 W		129 × 97 × 30			
		PMT-48V150W2BNJ 新品			3.3 A	158.4 W		159 × 97 × 30			
		PMT-48V200W2BNJ 新品			4.4 A	211.2 W		159 × 97 × 30			
		PMT-48V350W2BNJ 新品			7.3 A	350.4 W		215 × 115 × 30			
PMT2  <ul style="list-style-type: none"> • 紧凑设计 • 具备 IEC 60335 / IEC 61558 安规认证 • 50°C 满功率输出 • 低空载功耗 	PMT-12V35W2BA□		12 V	3.0 A	36 W	90-264 V _{AC}	99 × 82 × 29				
	PMT-12V50W2BA□			4.2 A	50.4 W		99 × 82 × 29				
	PMT-12V75W2BA□			6.0 A	72 W		99 × 97 × 30				
	PMT-12V100W2BA□			8.5 A	102 W		129 × 97 × 30				
	PMT-12V150W2BA□			12.5 A	150 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30				
	PMT-12V150W2CA□			12.5 A	150 W	90-264 V _{AC}	159 × 97 × 30				
	PMT-12V200W2BM□			17.0 A	204 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30				
	PMT-12V200W2BR□			17.0 A	204 W		159 × 97 × 30				
	PMT-12V350W2BM□			29.0 A	348 W		215 × 115 × 30				
	PMT-12V350W2BR□			29.0 A	348 W		215 × 115 × 30				
		PMT-15V35W2BA		15 V	2.4 A	36 W	90-264 V _{AC}	99 × 82 × 29			
		PMT-15V50W2BA			3.4 A	51 W		99 × 82 × 29			
		PMT-15V75W2BA			5.0 A	75 W		99 × 97 × 30			
		PMT-15V100W2BA			7.0 A	105 W	129 × 97 × 30				
		PMT-15V150W2BA			10.0 A	150 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30			
		PMT-15V150W2CA			10.0 A	150 W	90-264 V _{AC}	159 × 97 × 30			
		PMT-24V35W2BA□		24 V	1.5 A	36 W	90-264 V _{AC}	99 × 82 × 29			
		PMT-24V50W2BA□			2.2 A	52.8 W		99 × 82 × 29			
		PMT-24V75W2BA□			3.2 A	76.8 W		99 × 97 × 30			
		PMT-24V100W2BA□			4.5 A	108 W		129 × 97 × 30			
		PMT-24V150W2BA□			6.25 A	150 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30			
		PMT-24V150W2CA□			6.25 A	150 W	90-264 V _{AC}	159 × 97 × 30			
		PMT-24V200W2BM□			8.8 A	211.2 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30			
		PMT-24V200W2BR□			8.8 A	211.2 W		159 × 97 × 30			
		PMT-24V350W2BM□			14.6 A	350.4 W		215 × 115 × 30			
		PMT-24V350W2BR□			14.6 A	350.4 W		215 × 115 × 30			
					PMT-30V35W2BA		30 V	1.2 A	36 W	90-264 V _{AC}	99 × 82 × 29
					PMT-30V50W2BA			1.7 A	51 W		99 × 82 × 29
					PMT-30V75W2BA			2.5 A	75 W		99 × 97 × 30
					PMT-30V100W2BA			3.6 A	108 W	129 × 97 × 30	
PMT-30V150W2BA	5.0 A		150 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30						
PMT-30V150W2CA	5.0 A		150 W	90-264 V _{AC}	159 × 97 × 30						
	PMT-36V35W2BA		36 V	1.0 A	36 W	90-264 V _{AC}	99 × 82 × 29				
	PMT-36V50W2BA			1.45 A	52.2 W		99 × 82 × 29				
	PMT-36V75W2BA			2.1 A	75.6 W		99 × 97 × 30				
	PMT-36V100W2BA			3.0 A	108 W		129 × 97 × 30				
	PMT-36V150W2BA			4.3 A	154.8 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30				
	PMT-36V150W2CA			4.3 A	154.8 W	90-264 V _{AC}	159 × 97 × 30				

*对于可选项, 请参阅产品规格书

平板型电源

经济型

系列	型号名称*	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
PMT2  <ul style="list-style-type: none"> 紧凑设计 具备 IEC 60335 / IEC 61558 安规认证 50°C 满功率输出 低空载功耗 	PMT-36V200W2BM		36 V	5.9 A	212.4 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30
	PMT-36V200W2BR			5.9 A	212.4 W		159 × 97 × 30
	PMT-36V350W2BM			9.7 A	349.2 W		215 × 115 × 30
	PMT-36V350W2BR			9.7 A	349.2 W		215 × 115 × 30
	PMT-48V35W2BA		48 V	0.8 A	38.4 W	90-264V _{AC}	99 × 82 × 29
	PMT-48V50W2BA			1.1 A	52.8 W		99 × 82 × 29
	PMT-48V75W2BA			1.6 A	76.8 W		99 × 97 × 30
	PMT-48V100W2BA			2.3 A	110.4 W		129 × 97 × 30
	PMT-48V150W2BA			3.3 A	158.4 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30
	PMT-48V150W2CA			3.3 A	158.4 W	90-264V _{AC}	159 × 97 × 30
	PMT-48V200W2BM			4.4 A	211.2 W	90-132V _{AC} , 180-264V _{AC} (选择开关)	159 × 97 × 30
	PMT-48V200W2BR			4.4 A	211.2 W		159 × 97 × 30
	PMT-48V350W2BM		7.3 A	350.4 W	215 × 115 × 30		
	PMT-48V350W2BR		7.3 A	350.4 W	215 × 115 × 30		
	PMT-D1V75W2□A		5 V/12 V	5.0 A/4.0 A	73 W	90-264V _{AC}	129 × 97 × 30
	PMT-D2V75W2□A		5 V/24 V	5.0 A/2.1 A	75.4 W		129 × 97 × 30

高性能

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
PMR  <ul style="list-style-type: none"> 内建遥控开关 (≥ 600W) 内置 PFC 具备 IEC 60335 / IEC 61558 安规认证 1U 低高度 	PMR-12V150W1AT	●	12 V	12.5 A	150 W	90-264V _{AC} (直流输入范围 127-375V _{DC})	129 × 97 × 30
	PMR-12V240W1AT	●		20.0 A	240 W		159 × 97 × 30
	PMR-12V320W1AT	●		26.7 A	320.4 W		215 × 115 × 30
	PMR-12V600W1BT	●		50.0 A	600 W		225 × 124 × 41
	PMR-12V1K0W1BT	新品		60.0 A	720 W		225 × 124 × 41
	PMR-24V150W1AT	●	24 V	6.5 A	156 W	90-264V _{AC} (直流输入范围 127-375V _{DC})	129 × 97 × 30
	PMR-24V240W1AT	●		10.0 A	240 W		159 × 97 × 30
	PMR-24V320W1AT	●		13.4 A	321.6 W		215 × 115 × 30
	PMR-24V600W1BT	●		25.0 A	600 W		225 × 124 × 41
	PMR-24V1K0W1BT	新品		42.0 A	1,008 W		225 × 124 × 41
	PMR-24V1K5W1BTB	新品	62.5 A	1,500 W	90-264V _{AC}	204 × 127 × 40.5	
	PMR-36V150W1AT	●	36 V	4.3 A	154.8 W	90-264V _{AC} (直流输入范围 127-375V _{DC})	129 × 97 × 30
	PMR-36V240W1AT	●		6.7 A	241.2 W		159 × 97 × 30
	PMR-36V320W1AT	●		8.9 A	320.4 W		215 × 115 × 30
	PMR-36V600W1BT	●		16.6 A	597.6 W		225 × 124 × 41
	PMR-36V1K0W1BT	新品		28.0 A	1,008 W		225 × 124 × 41
	PMR-48V150W1AT	●	48 V	3.3 A	158.4 W	90-264V _{AC} (直流输入范围 127-375V _{DC})	129 × 97 × 30
	PMR-48V240W1AT	●		5.0 A	240 W		159 × 97 × 30
	PMR-48V320W1AT	●		6.7 A	321.6 W		215 × 115 × 30
	PMR-48V600W1BT	●		12.5 A	600 W		225 × 124 × 41
PMR-48V1K0W1BT	新品	21.0 A		1,008 W	225 × 124 × 41		
PMR-48V1K5W1BTC	新品	31.25 A	1,500 W	90-264V _{AC}	204 × 127 × 40.5		

特别设计

系列	型号名称	PFC	输出			输入电压范围	尺寸 (毫米) (L × W × H)
			电压	电流	功率		
PMS  <ul style="list-style-type: none"> 主动式并联均流功能 内建 PMBus® 通讯功能 峰值功率, 适用于电机 最多支持 6 台并联以提高输出功率 	PMS-12V2K5W1BTD	新品	12 V	208.3 A	2,500 W	85-264V _{AC}	271 × 127 × 40.5
	PMS-24V750W1BTD	新品		31.25 A	750 W		85-264V _{AC}
	PMS-24V1K2W1BTD	新品	24 V	50.0 A	1,200 W	204 × 127 × 40.5	
	PMS-24V2K5W1BTD	新品		104.2 A	2,500 W	271 × 127 × 40.5	
	PMS-48V750W1BTD	新品	48 V	15.63 A	750 W	85-264V _{AC}	
	PMS-48V1K2W1BTD	新品		25.0 A	1,200 W		204 × 127 × 40.5
PMS-48V2K5W1BTD	新品	52.1 A		2,500 W	271 × 127 × 40.5		

*对于可选项, 请参阅产品规格书