

# Product Selection Guide

New products are frequently introduced. Please visit [www.DeltaPSU.com](http://www.DeltaPSU.com) for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range	
			1						
Panel Mount Power Supply	PMT2 • IEC 60335, IEC 61558 approvals • Low profile 30mm height	PMT-12V35W2BA□	●		12 V	3.0 A	36 W	90-264 V <sub>AC</sub>	
		PMT-12V50W2BA□	●			4.2 A	50.4 W		
		PMT-12V75W2BA□	●			6.0 A	72 W		
		PMT-12V100W2BA□	●			8.5 A	102 W		
		PMT-12V150W2BA□	●			12.5 A	150 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-12V150W2CA□	●			12.5 A	150 W		
		PMT-12V200W2BM□	●			17.0 A	204 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-12V200W2BR□	●			17.0 A	204 W		
		PMT-12V350W2BM□	●		29.0 A	348 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)		
		PMT-12V350W2BR□	●		29.0 A	348 W			
		PMT-15V35W2BA	●		15 V	2.4 A	36 W	90-264 V <sub>AC</sub>	
		PMT-15V50W2BA	●			3.4 A	51 W		
		PMT-15V75W2BA	●			5.0 A	75 W		
		PMT-15V100W2BA	●			7.0 A	105 W		
		PMT-15V150W2BA	●		10.0 A	150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)		
		PMT-15V150W2CA	●						
		PMT-24V35W2BA□	●		24 V	1.5 A	36 W	90-264 V <sub>AC</sub>	
		PMT-24V50W2BA□	●			2.2 A	52.8 W		
		PMT-24V75W2BA□	●			3.2 A	76.8 W		
		PMT-24V100W2BA□	●			4.5 A	108 W		
		PMT-24V150W2BA□	●			6.25 A	150 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-24V150W2CA□	●			6.25 A	150 W		
		PMT-24V200W2BM□	●			8.8 A	211.2 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-24V200W2BR□	●			8.8 A	211.2 W		
		PMT-24V350W2BM□	●		14.6 A	350.4 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)		
		PMT-24V350W2BR□	●		14.6 A	350.4 W			
		PMT-30V35W2BA	●		30 V	1.2 A	36 W	90-264 V <sub>AC</sub>	
		PMT-30V50W2BA	●			1.7 A	51 W		
		PMT-30V75W2BA	●			2.5 A	75 W		
		PMT-30V100W2BA	●			3.6 A	108 W		
		PMT-30V150W2BA	●		5.0 A	150 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)		
		PMT-30V150W2CA	●						
		PMT-36V35W2BA	●		36 V	1.0 A	36 W	90-264 V <sub>AC</sub>	
		PMT-36V50W2BA	●			1.45 A	52.2 W		
		PMT-36V75W2BA	●			2.1 A	75.6 W		
		PMT-36V100W2BA	●			3.0 A	108 W		
		PMT-36V150W2BA	●			4.3 A	154.8 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-36V150W2CA	●			4.3 A	154.8 W		
		PMT-36V200W2BM	●			5.9 A	212.4 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-36V200W2BR	●			5.9 A	212.4 W		
		PMT-36V350W2BM	●		9.7 A	349.2 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)		
		PMT-36V350W2BR	●		9.7 A	349.2 W			
		PMT-48V35W2BA	●		48 V	0.8 A	38.4 W	90-264 V <sub>AC</sub>	
		PMT-48V50W2BA	●			1.1 A	52.8 W		
		PMT-48V75W2BA	●			1.6 A	76.8 W		
		PMT-48V100W2BA	●			2.3 A	110.4 W		
		PMT-48V150W2BA	●			3.3 A	158.4 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMT-48V150W2CA	●			3.3 A	158.4 W		
PMT-48V200W2BM	●		4.4 A	211.2 W		90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)			
PMT-48V200W2BR	●		4.4 A	211.2 W					
PMT-48V350W2BM	●		7.3 A	350.4 W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)				
PMT-48V350W2BR	●		7.3 A	350.4 W					

## Model Numbering

PM	T -	XXV	XXXW	2	□	□	CC Code
Panel Mount	Product Type T - Enclosed	Output Voltage	Output Power	Single Phase with Low Profile	Family Code For 35-100W B - No PFC, universal input voltage range For 150-350W B - No PFC, input voltage selectable by switch C - No PFC, universal input voltage range	Connector Type Terminal Block A - With TUV, UL, CE, CCC, KC, EAC M - With UL, EAC R - With TUV, UL, CE, EAC	Blank - Without connector cover B - With conformal coating <sup>1)</sup>

# Product Selection Guide

New products are frequently introduced. Please visit [www.DeltaPSU.com](http://www.DeltaPSU.com) for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*
			1					
Panel Mount Power Supply	PMT2 • IEC 60335, IEC 61558 approvals • Low profile 30mm height	PMT-D1V75W2□A	•		5V/12V	5.0A/4.0A	73W	90-264 V <sub>AC</sub>
		PMT-D2V75W2□A	•		5V/24V	5.0A/2.1A	75.4W	90-264 V <sub>AC</sub>
	PMC • Universal AC input voltage	PMC-05V015W1AA	•		5V	3.0A	15W	85-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )
		PMC-12V150W1B□	•	•	12V	12.5A	150W	85-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )
		PMC-12V600W1BA	•	•		50.0A	600W	85-264 V <sub>AC</sub> (DC input range 120-370 V <sub>DC</sub> )
		PMC-24V150W1B□	•	•	24V	6.25A	150W	85-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )
		PMC-24V300W1BA	•	•		V1: 12.5A V2 <sub>SB</sub> : 0.5A	300W	
		PMC-24V600W1BA	•	•		25.0A	600W	85-264 V <sub>AC</sub> (DC input range 120-370 V <sub>DC</sub> )
		PMC-24V600W1RW	•	•		25.0A	600W	85-264 V <sub>AC</sub>
		PMC-48V150W1BA	•	•	48V	3.125A	150W	85-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )
		PMC-48V600W1BA	•	•		12.5A	600W	85-264 V <sub>AC</sub> (DC input range 120-370 V <sub>DC</sub> )
		PMC-DSPV100W1A	•		24V/5V	2.7A/7.0A	100W	85-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )
	PMF • Remote ON/OFF • Built-in PFC	PMF-4V320WC□□	•	•	4.2V	55.0A	231W	88-264 V <sub>AC</sub>
		PMF-5V320WC□□	•	•	5V	55.0A	275W	88-264 V <sub>AC</sub>
		PMF-24V240WC□□	•	•	24V	10.0A	240W	88-264 V <sub>AC</sub>
		PMF-24V320WC□□	•	•		13.3A	320W	88-264 V <sub>AC</sub>

\* DC input is certified for selected models

## Model Numbering

PM	T –	XXV	XXXW	2	□	A
Panel Mount	Product Type T - Enclosed	Output Voltage Dual Output D1 - 5V / 12V D2 - 5V / 24V	Output Power	Single Phase with Low Profile	Family Code B - No PFC, Non-Isolated C - No PFC, Isolated	Connector Type A - Terminal Block

1) Options for 12V and 24V models only

PM	C –	XXV	XXXW	1	□	□
Panel Mount	Product Type C - Enclosed	Output Voltage	Output Power	Phase Input 1 - Single Phase, Wide Range Input Voltage	A - No PFC B - With PFC R - With PFC, Remote ON/OFF, Remote Sense	Connector Type A - Terminal Block <sup>1)</sup> J - IP20 Connector <sup>2)</sup> L - Front Face <sup>2)</sup> W - Front Face with conformal coating
PM	C –	D	SPV	100W	1	A
Panel Mount	Product Type C - Enclosed	Dual Output	Output Voltage S - 24V P - 5V	Output Power	Phase Input 1 - Single Phase	A - Delta Standard

1) For PMC-05V015W1AA and PMC-□V600W1BA, the connector type is a Front Face connector. For PMC-24V300W1BA, the connector type is an IP20 connector.

2) Options

PM	F –	XXV	XXXW	C	□	□
Panel Mount	Product Series F - PFC Series	Output Voltage	Output Power	Package Type C - Enclosed	Connector Type G - Front Face A - Terminal Block <sup>1)</sup>	Variable B - No Remote ON/OFF R - With Remote ON/OFF <sup>1)</sup>

1) Options

# Product Selection Guide

New products are frequently introduced. Please visit [www.DeltaPSU.com](http://www.DeltaPSU.com) for latest product updates.

Product Type	Series	Model Name	Phase		Output Voltage	Output Current	Output Power	Input Voltage Range*
			1	PFC				
Panel Mount Power Supply	PMR • Thickness < 1U • Built-in PFC	PMR-4V320WC□A	•	•	4.2V	60.0A	252W	88-264 V <sub>AC</sub>
		PMR-4V320WDAA	•	•		60.0A	252W	
		PMR-4V320WDGA	•	•		60.0A	252W	
		PMR-4V320WDBA	•	•		60.0A	252W	
		PMR-4V320WDCA	•	•		60.0A	252W	
		PMR-5V320WC□A	•	•	5V	60.0A	300W	88-264 V <sub>AC</sub>
		PMR-5V320WDAA	•	•		60.0A	300W	
		PMR-5V320WDGA	•	•		60.0A	300W	
		PMR-5V320WDBA	•	•		60.0A	300W	
		PMR-5V320WDCA	•	•		60.0A	300W	
	NEW PMR-12V320W1AT	•	•	12V	26.7A	320.4W	90-264 V <sub>AC</sub>	
	NEW PMR-24V320W1AT	•	•	24V	13.4A	321.6W	90-264 V <sub>AC</sub>	
	NEW PMR-36V320W1AT	•	•	36V	8.9A	320.4W	90-264 V <sub>AC</sub>	
	NEW PMR-48V320W1AT	•	•	48V	6.7A	321.6W	90-264 V <sub>AC</sub>	
	PMU • Power supply with integrated DC-UPS	PMU-13V155W□BA	•	•	13.8V	V1: 9.5A B+: 1.5A	151W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMU-13V155W□CA	•	•			151W	
		PMU-27V155W□BA	•	•	27.6V	Enclosed L Frame V1: 4.0A, B+: 1.5A V1: 4.3A, B+: 1.2A	151W	90-132 V <sub>AC</sub> , 180-264 V <sub>AC</sub> (Selectable by Switch)
		PMU-27V155W□CA	•	•			151W	
	MEB • Intelligent Fan Speed Control	NEW MEB-750A12B AAA	•	•	12V	58.4A	750W	85-264 V <sub>AC</sub>
		NEW MEB-750A12T AAA	•	•				
		MEB-500A24F AA	•	•	24V	21.0A	500W	90-264 V <sub>AC</sub>
		MEB-750A24B AAA	•	•		31.25A	750W	85-264 V <sub>AC</sub>
		MEB-750A24T AAA	•	•		31.25A	750W	
		MEB-750A48B AAA	•	•	48V	15.63A	750W	85-264 V <sub>AC</sub>
		MEB-750A48T AAA	•	•		15.63A	750W	
		MEB-1K2A24T ABA	•	•	24V	50.0A	1,200W	85-264 V <sub>AC</sub>
		MEB-1K2A42T ABA	•	•	42V	28.5A	1,200W	85-264 V <sub>AC</sub>
		MEB-1K2A48T ABA	•	•	48V	25.0A	1,200W	85-264 V <sub>AC</sub>

\* DC input is certified for selected models

## Model Numbering

PM	R -	XXV	XXXW	□	□	A
Panel Mount	Product Series R - Standard Rack Type Series (1U)	Output Voltage	Output Power	Package Type C - Enclosed with Fan D - Enclosed without Fan	Connector Type A - Terminal Block B - Terminal Block (Parallel Operation) <sup>1)</sup> G - Front Face <sup>2)</sup> C - Front Face (Parallel Operation) <sup>1)</sup>	Variable A - With conformal coating

1) Options for Enclosed without Fan (PMR-□V320WDBA and PMR-□V320WDCA)

2) Options

PM	R -	XXV	XXXW	1	A	T
Panel Mount	Product Series R - Standard Rack Type Series (1U)	Output Voltage	Output Power	Phase Input 1 - Single Phase	Family Code A - Family A	Variable T - Terminal Block

ME	B -	XXX	A	□	□	□□□
Delta Medical Power Supply	B - Enclosed	Max power wattage in the product series. May be lower at some conditions.	Family Code	Output Voltage	Input Connector Type	CC Code
		500 - 500W	A - Family A	24 - 24V	F - Front Face	AA - With Remote ON/OFF, with conformal coating
		750 - 750W		12 - 12V 24 - 24V 48 - 48V	B - C14 T - US Terminal	AAA - With Remote ON/OFF, with conformal coating
		1K2 - 1,200W		24 - 24V 42 - 42V 48 - 48V	T - US Terminal	ABA - With Remote ON/OFF, with conformal coating